

Certificate
2607741 (2)



Issued 21-08-2026
Valid until See Appendix

Kiwa Type 3 Thermostatic Mixing Valve and KUKReg4 Certification

Kiwa hereby declares that legitimate confidence exists in the products specified and model number(s) listed in the Appendix for:

Delabie

meets the requirements as described in the
Evaluation Guideline - Kiwa UK – EG001⁽¹⁾ – Thermostatic mixing valves
Evaluation Guideline – Kiwa UK – EG004⁽²⁾ – Regulation 4(1)(a)

Which verifies the requirements of reference standard(s):

The DoH: Health Technical Memorandum 04-01: Supplement Performance specification D 08: thermostatic mixing valves (healthcare premises) 2017.

Regulation 4(1)(a) of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification and is only valid in combination with the appendix.

David Jay
Business Unit Manager- Authorised
Signatory Kiwa Limited (Watertec)

This certificate relates to products intended to be used in the UK only. For other countries, other (National) requirements will apply.

Disclosure of the certificate is permitted in full.

⁽¹⁾ ⁽²⁾ see appendix for reference to relevant Evaluation Guideline version associated with the certification

To check the validity of a certificate, scan the QR code or go to [TMVs certificate search](#)



Appendix

The following products belong to this certificate

Reference:	2607741, S2404126 ⁽¹⁾ EG Issue 8 ⁽²⁾ EG Issue 7 expires 31/07/2031
Product description:	Range of sequential deck mounted thermostatic mixing valves. The assembly has various configurations, see models below. The outlet is fitted with a plastic flow straightener. The supply inlets are supplied with a servicing valve that incorporates a flow regulator, water supply can be via either copper or flexible PEX pipes fitted with stainless steel strainer.
Models:	H9600 Flexible tails fixed H9605 Flexible tails Bioclip H960015 Flexible tails fixed H960515 Flexible tails Bioclip H960515L Flexible tails Bioclip H9600610 Copper tails fixed H9605610 Copper tails Bioclip H9605610L Copper tails Bioclip
Size:	10mm/3/8.
Designation of Use:	HP-WE LP-WE
Marking:	Facia ring (after the removal of the handle) embossed Delabie and 96-W. Handle laser etched Delabie. Inlet connections/tube marked red and blue.
Materials:	Non-metallic materials assessed (BS 6920) to the point of discharge.
Backflow protection notes:	Fit SCV at each inlet.

Reference:	2608731, S2404042 ⁽¹⁾ EG Issue 8 ⁽²⁾ EG Issue 7 expires 21/08/2031
Product description:	Range of wall or deck mounted sequential thermostatic valves. The assembly has various configurations, see models below. Spouts have Bioclip feature and are fitted with a plastic flow straightener The supply inlets incorporate a strainer and flow restrictor.
Models:	H9611P Securitherm, wall mounted ctrs 150mm H9614P Securitherm, wall mounted ctrs 200mm H9615 Securitherm, pillar mounted, ctrs 200mm
Size:	1/2 BSP male
Designation of Use:	HP-WE
Marking:	Facia ring (after the removal of the handle) embossed Delabie and 96-W. Handle laser etched Delabie. Underside of valve body marked H (hot) and WF.
Materials:	Non-metallic materials assessed (BS 6920) to the point of discharge.
Backflow protection notes:	Fit SCV at each inlet.
Additional note:	Label on box gives a QR code that directs to the valve's installation and maintenance document.